

View Online at <https://aerobasegroup.com/nsn/5310-01-040-4730>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.194 inches nut

Lubrication:

Dry film lubricant

Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Nut Style:

Plate

Nut Length:

0.521 inches

Nut Height:

0.250 inches

Plate Thickness:

0.047 inches

Plate Width:

0.437 inches

Nut Counterbore Depth:

0.062 inches nut

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.245 inches and 0.255 inches

Center To Center Distance Between Mounting Holes Along Width:

Between 0.217 inches and 0.221 inches

Temperature Rating:

450.0 degrees fahrenheit

Thread Series:

Unjf

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Material:

Steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541 or steel comp 1042 or steel comp 1043 or steel comp 1044 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel comp 1050 or steel comp 1551 or steel comp 1552 or steel comp 1053 or steel comp 1055 or steel comp 1059 or steel comp 1060 or steel comp 1561 or steel comp 1064 or

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, class 3 federal specification single treatment response

Specification Data:

81205-bacn10jp manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0