

View Online at https://aerobasegroup.com/nsn/5310-01-044-0758

Thread Class: 3b Thread Direction: Right-hand Locking Feature: Prevailing torque all metal design Counterbore Diameter: 0.254 inches nut Lubrication: Dry film lubricant Overall Length: 72.000 inches Overall Width: 0.534 inches Nut Style: A20 gang channel, self locking Channel Style: Straight type Assemblyheight: 0.472 inches Channel Height: 0.203 inches Nut Spacing: 1.500 inches Nut Spacing: 1.500 inches Nut Counterbore Depth: 0.240 inches and 0.260 inches nut Nut Quantity: 48 Thread Series: Unf Features Provided: Floating nut
Tread Direction: Right-hand Locking Feature: Prevailing torque all metal design Counterbore Diameter: 0.254 inches nut Lubrication: Dyry film lubricant Overall Length: 72.000 inches Overall Width: 0.534 inches Nut Style: A20 gang channel, self locking Channel Style: Straight type Assemblyheight: 0.472 inches Nut Spacing: 1.500 inches Nut Spacing: 1.500 inches Nut Spacing: 1.500 inches Nut Quentity: 0.472 inches Nut Spacing: 1.500 inches Nut Quentity: 0.240 inches and 0.260 inches nut Nut Quentity: 48 Thread Series: Unf Fieatures Provided: Fioating nut
Right-hand Locking Feature: Prevailing torque all metal design Counterbore Diameter: 0.254 linches nut Lubrication: Dry film lubricant Overall Length: 7.000 inches Overall Width: 0.534 inches Nut Style: A20 gang channel, self locking Channel Style: Straigh type Assemblyheight: 0.203 inches Nut Spacing: 1.500 inches
Locking Feature: Prevailing torque all metal design Counterbore Diameter: 0.254 inches nut Lubrication: Dy film lubricant Overall Length: 72.000 inches Overall Width: 0.534 inches Nut Style: A20 gang channel, self locking Channel Style: Straight type Assemblyheight: 0.203 inches Nut Style: 0.203 inches Channel Height: 0.203 inches Nut Spacing: 1.500 inches Nut Counterbore Depth: 0.240 inches and 0.260 inches nut Nut Quantity: 48 Thread Series: Urf Fleatures Provided: Floating nut
Prevailing torque all metal designCounterbore Diameter:0.254 inches nutLubrication:Dy film lubricantOverall Length:72.000 inchesOverall Width:0.534 inchesNut Style:A20 gang channel, self lockingChannel Style:Straight typeAssemblyheight:0.203 inchesNut Style:0.472 inchesChannel Height:0.203 inchesNut Style:0.203 inchesNut Style:0.203 inchesNut Style:0.204 inchesNut Style:1.500 inchesNut Counterbore Depth:0.240 inches and 0.260 inches nutNut Quantity:48Thread Series:UnfFeatures Provided:Floating nut
Counterbore Diameter: 0.254 inches nut Lubrication: Dry film lubricant Overall Length: 72.000 inches Overall Width: 0.534 inches Nut Style: A20 gang channel, self locking Channel Style: Straight type Assemblyheight: 0.472 inches Channel Height: 0.203 inches Nut Spacing: 1.500 inches Nut Spacing: 1.500 inches Nut Counterbore Depth: 0.240 inches nut Nut Quantity: 48 Thread Series: Unf Fieatures Provided: Fioating nut
0.254 inches nut Lubrication: Ury film lubricant Overall Length: C.2000 inches Coverall Width: C.304 inches Coverall Width: C.334 inches Coverall Width: C.334 inches Coverall Width: C.334 inches Coverall Width: C.334 inches Coverall Style: C.334 inches C.334 inch
Lubrication:Dry film lubricantOverall Length:72.000 inchesOverall Width:0.534 inchesNut Style:A20 gang channel, self lockingChannel Style:Straight typeAssemblyheight:0.472 inchesChannel Height:0.203 inchesNut Style:0.203 inchesNut Style:0.203 inchesNut Style:0.203 inchesNut Counterbore Depth:0.240 inches and 0.260 inches nutNut Quantity:48Thread Series:UnfFeatures Provided:Floating nut
Dry film lubricantOverall Length:72.000 inchesOverall Width:0.534 inchesNut Style:A20 gang channel, self lockingChannel Style:Straight typeAssemblyheight:0.472 inchesChannel Height:0.203 inchesNut Spacing:1.500 inchesNut Counterbore Depth:0.240 inches and 0.260 inches nutNut Quantity:48Thread Series:UnfFeatures Provided:Floating nut
Overall Length:72.000 inchesOverall Width:0.534 inchesNut Style:A20 gang channel, self lockingChannel Style:Straight typeAssemblyheight:0.472 inchesChannel Height:0.203 inchesNut Spacing:1.500 inchesNut Counterbore Depth:0.240 inches and 0.260 inches nutNut Quantity:48Thread Series:UnfFeatures Provided:Floating nut
72.000 inchesOverall Width:0.534 inchesNut Style:A20 gang channel, self lockingChannel Style:Straight typeAssemblyheight:0.472 inchesChannel Height:0.203 inchesNut Spacing:1.500 inchesNut Counterbore Depth:0.240 inches and 0.260 inches nutNut Quantity:48Thread Series:UnfFeatures Provided:Floating nut
Overall Width:0.534 inchesNut Style:A20 gang channel, self lockingChannel Style:Straight typeAssemblyheight:0.472 inchesChannel Height:0.203 inchesNut Spacing:1.500 inchesNut Counterbore Depth:0.240 inches and 0.260 inches nutNut Quantity:48Thread Series:UnfFeatures Provided:Floating nut
0.534 inches Nut Style: A20 gang channel, self locking Channel Style: Straight type Assemblyheight: 0.472 inches Channel Height: 0.472 inches Channel Height: 0.203 inches Nut Spacing: 1.500 inches Nut Spacing: 1.500 inches and 0.260 inches nut Nut Quantity: 48 Thread Series: Unf Features Provided: Floating nut
Nut Style:A20 gang channel, self lockingChannel Style:Straight typeAssemblyheight:0.472 inchesChannel Height:0.203 inchesNut Spacing:1.500 inchesNut Counterbore Depth:0.240 inches and 0.260 inches nutNut Quantity:48Thread Series:UnfFeatures Provided:Floating nut
A20 gang channel, self locking Channel Style: Straight type Assemblyheight: 0.472 inches Channel Height: 0.203 inches 0.203 inches Nut Spacing: 1.500 inches Nut Counterbore Depth: 0.240 inches and 0.260 inches nut Nut Quantity: 48 Thread Series: Unf Features Provided: Floating nut
Channel Style: Straight type Assemblyheight: 0.472 inches Channel Height: 0.203 inches Nut Spacing: 1.500 inches Nut Counterbore Depth: 0.240 inches and 0.260 inches nut Nut Quantity: 48 Thread Series: Unf Features Provided: Floating nut
Straight type Assemblyheight: 0.472 inches Channel Height: 0.203 inches 0.203 inches Nut Spacing: 1.500 inches Nut Counterbore Depth: 0.240 inches and 0.260 inches nut Nut Quantity: 48 Thread Series: Unf Features Provided: Floating nut
Assemblyheight: 0.472 inches Channel Height: 0.203 inches Nut Spacing: 1.500 inches Nut Counterbore Depth: 0.240 inches and 0.260 inches nut Nut Quantity: 48 Thread Series: Unf Features Provided: Floating nut
0.472 inches Channel Height: 0.203 inches Nut Spacing: 1.500 inches Nut Counterbore Depth: 0.240 inches and 0.260 inches nut Nut Quantity: 48 Thread Series: Unf Features Provided: Floating nut
Channel Height: 0.203 inches Nut Spacing: 1.500 inches Nut Counterbore Depth: 0.240 inches and 0.260 inches nut Nut Quantity: 48 Thread Series: Unf Features Provided: Floating nut
0.203 inches Nut Spacing: 1.500 inches 1.500 inches Nut Counterbore Depth: 0.240 inches and 0.260 inches nut Nut Quantity: 48 Thread Series: Unf Features Provided: Floating nut
1.500 inches Nut Counterbore Depth: 0.240 inches and 0.260 inches nut Nut Quantity: 48 Thread Series: Unf Features Provided: Floating nut
Nut Counterbore Depth: 0.240 inches and 0.260 inches nut Nut Quantity: 48 Thread Series: Unf Features Provided: Floating nut
0.240 inches and 0.260 inches nut Nut Quantity: 48 Thread Series: Unf Features Provided: Floating nut
Nut Quantity: 48 Thread Series: Unf Features Provided: Floating nut
48 Thread Series: Unf Features Provided: Floating nut
Thread Series: Unf Features Provided: Floating nut
Unf Features Provided: Floating nut
Features Provided: Floating nut
Floating nut
Thready Qty Per Inch (tpi):
28
Thread Size:
0.250 inches
0.250 inches Material:
Material:
Material: Stainless steel

Passivate channel



Specification Data:

76301-st3-724 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0