

View Online at <https://aerobasegroup.com/nsn/5310-01-049-7357>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Lubrication:

Soluble lubricant

Nut Style:

Castellated, hexagon

Nut Height:

Between 0.345 inches and 0.365 inches

End Application:

W/s: aircraft, stratolifter c-135; aircraft, hercules c-130; support equipment, a-10 aircraft; helicopter, black hawk uh-60a; helicopter, electronic countermeasures, eh-60a; hh-60l medivac; aircraft, thunderbolt ii, a-10; aircraft, f-16

Width Across Flats:

Between 0.367 inches and 0.387 inches

Tempurature Rating:

1200.0 degrees fahrenheit

Thread Series:

Unf

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Bearing Surface Type:

Chamfered or washer faced

Material:

Steel uns s34720 or steel uns s34723 or steel comp 347

Material Specification:

Ams 5642 assn standard single material response or ams 5646 assn standard single material response

Surface Treatment:

Silver

Surface Treatment Specification:

Ams 2410 assn standard single treatment response or ams 2411 assn standard single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0