

View Online at <https://aerobasegroup.com/nsn/5310-01-050-4258>

Hole Diameter:

Between 0.261 inches and 0.313 inches

Outside Diameter:

Between 0.763 inches and 0.793 inches

Overall Height:

0.105 inches

Recess Diameter:

Between 0.507 inches and 0.527 inches

Material Thickness:

Between 0.014 inches and 0.018 inches

Recess Angle:

Between 99.0 degrees and 103.0 degrees

Material:

Steel comp 1008 or steel comp 1009 or steel comp 1015 or steel comp 1018 or steel comp 1020 or steel comp 1025 or steel comp 1010

Material Specification:

Qq-s-698, cond 1/2 h or hard federal specification 1st material response or qq-s-698, cond 1/2 h or hard federal specification 2nd material response or qq-s-698, cond 1/2 h or hard federal specification 3rd material response or qq-s-698, cond 1/2 h or hard federal specification 4th material response or qq-s-698, cond 1/2 h or hard federal specification 5th material response or mil-s-7952 military specification 5th material response or mil-s-7952 military specification 6th material response or sae assn standard 7th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 1 federal specification single treatment response

Style Designator:

Finishing

Specification Data:

81205-bacw10u manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A022b0

Mil-std (military Standard):

Mil-s-7952 spec.