

View Online at <https://aerobasegroup.com/nsn/5310-01-053-3363>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Lubrication:**

Dry film lubricant

**Mounting Hole Diameter:**

Between 0.125 inches and 0.130 inches

**Nut Style:**

Plate

**Nut Length:**

1.115 inches

**Nut Height:**

Between 0.590 inches and 0.630 inches

**Plate Thickness:**

Between 0.025 inches and 0.035 inches

**Plate Width:**

Between 0.545 inches and 0.575 inches

**Removable Nut Manufacturer Code:**

29372

**Nut Mounting Provision:**

Straight holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.435 inches and 0.440 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.873 inches and 0.877 inches

**Removable Nut Manufacturer Part Number:**

Ca21024-1

**Thread Series:**

Unf

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Material:**

Stainless steel shell

**Material Specification:**

Mil-s-6049 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut

**Surface Treatment:**

Passivate shell

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0

**Mil-std (military Standard):**

Mil-s-6049 spec.