

View Online at <https://aerobasegroup.com/nsn/5310-01-053-3363>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Lubrication:

Dry film lubricant

Mounting Hole Diameter:

Between 0.125 inches and 0.130 inches

Nut Style:

Plate

Nut Length:

1.115 inches

Nut Height:

Between 0.590 inches and 0.630 inches

Plate Thickness:

Between 0.025 inches and 0.035 inches

Plate Width:

Between 0.545 inches and 0.575 inches

Removable Nut Manufacturer Code:

29372

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.435 inches and 0.440 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.873 inches and 0.877 inches

Removable Nut Manufacturer Part Number:

Ca21024-1

Thread Series:

Unf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Material:

Stainless steel shell

Material Specification:

Mil-s-6049 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut

Surface Treatment:

Passivate shell

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-s-6049 spec.