

NSN 5310-01-056-2177 Blind Rivet Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-01-056-2177 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Eliptical countersunk **Head Height:** 0.054 inches **Locking Feature:** Prevailing torque all metal design **Head Major Diameter:** Between 0.704 inches and 0.708 inches **Head Minor Diameter:** Between 0.598 inches and 0.602 inches Lubrication: Dry film lubricant **Nut Style:** Blind rivet w/smooth round shank **Nut Diameter:** Between 0.537 inches and 0.539 inches **Nut Length:** 1.158 inches **Nut Grip Range:** +0.400/+0.460 inches **Shank End Type:** Open **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unif

Thready Qty Per Inch (tpi):

20

Thread Size:

0.438 inches

**Head Major Countersink Angle:** 

Between 75.75 degrees and 76.25 degrees

**Head Minor Countersink Angle:** 

Between 59.75 degrees and 60.25 degrees

Material:

Steel comp 304 or steel comp 305

**Material Specification:** 

Qq-s-763 cond a federal specification all material responses

## NSN 5310-01-056-2177

Blind Rivet Self-locking Nut - Page 2 of 2



Surface Treatment:	
Cadmium	and chromate

**Surface Treatment Specification:** 

Q-p-416, type 2 class 2 assn standard 13th treatment response

**Specification Data:** 

80205-nas1734 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A021a0