

NSN 5310-01-056-2179 Blind Rivet Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-01-056-2179 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Eliptical countersunk **Head Height:** 0.054 inches **Locking Feature:** Prevailing torque all metal design **Head Major Diameter:** Between 0.704 inches and 0.708 inches **Head Minor Diameter:** Between 0.598 inches and 0.602 inches Lubrication: Dry film lubricant **Nut Style:** Blind rivet w/smooth round shank **Nut Diameter:** Between 0.537 inches and 0.539 inches **Nut Length:** 1.278 inches **Nut Grip Range:** +0.520/+0.580 inches **Shank End Type:** Open **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unif

Thread Size:

0.438 inches

Head Major Countersink Angle:

Thready Qty Per Inch (tpi):

Between 75.75 degrees and 76.25 degrees

Head Minor Countersink Angle:

Between 59.75 degrees and 60.25 degrees

Material:

Steel comp 304 or steel comp 305

Material Specification:

Qq-s-763 cond a federal specification all material responses

NSN 5310-01-056-2179

Blind Rivet Self-locking Nut - Page 2 of 2



| Surface Treatment | : |
|-------------------|---|
|-------------------|---|

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Specification Data:

80205-nas1734 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0