

NSN 5310-01-056-3228 Blind Rivet Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-01-056-3228 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Eliptical countersunk **Head Height:** 0.048 inches **Locking Feature:** Prevailing torque all metal design **Head Major Diameter:** Between 0.6016 inches and 0.6247 inches **Head Minor Diameter:** 0.5050 inches Lubrication: Dry film lubricant **Nut Style:** Blind rivet w/smooth round shank **Nut Diameter:** Between 0.469 inches and 0.471 inches **Nut Length:** 1.297 inches **Nut Grip Range:** +0.640/+0.700 inches **Shank End Type:** Open **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unif Thready Qty Per Inch (tpi):

Thread Size:

0.375 inches

**Head Major Countersink Angle:** 

Between 75.75 degrees and 76.25 degrees

**Head Minor Countersink Angle:** 

Between 59.75 degrees and 60.25 degrees

Material:

Steel comp 304 or steel comp 305

**Material Specification:** 

Qq-s-763, cond a federal specification all material responses

## NSN 5310-01-056-3228

Blind Rivet Self-locking Nut - Page 2 of 2



_	•	_		
SI.	rtac	e Tre	aatm	ont.
Ju	IIac	- 116	zauii	CIIL.

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2, class 2 federal specification all treatment responses

**Specification Data:** 

80205-nas1734 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A021a0