Blind Rivet Self-locking Nut - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5310-01-056-3235



Thread Class: 3b **Thread Direction: Right-hand** Head Style: Eliptical countersunk **Head Height:** 0.048 inches Locking Feature: Prevailing torque all metal design Head Major Diameter: Between 0.621 inches and 0.625 inches **Head Minor Diameter:** Between 0.524 inches and 0.528 inches Lubrication: Dry film lubricant Nut Style: Blind rivet w/smooth round shank Nut Diameter: Between 0.469 inches and 0.471 inches Nut Length: 1.177 inches Nut Grip Range: +0.520/+0.580 inches Shank End Type: Open **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unif Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches Head Major Countersink Angle: Between 75.75 degrees and 76.25 degrees Head Minor Countersink Angle: Between 59.75 degrees and 60.25 degrees Material: Steel comp 304 or steel comp 305 **Material Specification:**

Qq-s-763, cond a federal specification all material responses

NSN 5310-01-056-3235

Blind Rivet Self-locking Nut - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response except threads

Specification Data:

80205-nas1734 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0