Blind Rivet Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-056-5486

Thread Class:
3b
Thread Direction:
Right-hand
Head Style:
Eliptical countersunk
Head Height:
0.054 inches
Locking Feature:
Prevailing torque all metal design
Head Major Diameter:
Between 0.704 inches and 0.708 inches
Head Minor Diameter:
Between 0.598 inches and 0.602 inches
Lubrication:
Dry film lubricant
Nut Style:
Blind rivet w/smooth round shank
Nut Diameter:
Between 0.537 inches and 0.539 inches
Nut Length:
0.978 inches
Nut Grip Range:
+0.220/+0.280 inches
Shank End Type:
Open
Tempurature Rating:
450.0 degrees fahrenheit
Thread Series:
Unjf
Thready Qty Per Inch (tpi):
20
Thread Size:
0.438 inches
Head Major Countersink Angle:
Between 75.75 degrees and 76.25 degrees
Head Minor Countersink Angle:
Between 59.75 degrees and 60.25 degrees
Material:
Steel comp 304 or steel comp 305
Material Specification:
Qq-s-763, cond a federal specification all material responses

## NSN 5310-01-056-5486

Blind Rivet Self-locking Nut - Page 2 of 2



Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

**Specification Data:** 

80205-nas1734 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A021a0