

View Online at <https://aerobasegroup.com/nsn/5310-01-056-5487>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Head Style:**

Elliptical countersunk

**Head Height:**

0.048 inches

**Locking Feature:**

Prevailing torque all metal design

**Head Major Diameter:**

Between 0.621 inches and 0.625 inches

**Head Minor Diameter:**

Between 0.524 inches and 0.528 inches

**Lubrication:**

Dry film lubricant

**Nut Style:**

Blind rivet w/smooth round shank

**Nut Diameter:**

Between 0.469 inches and 0.471 inches

**Nut Length:**

1.057 inches

**Nut Grip Range:**

+0.400/+0.460 inches

**Shank End Type:**

Open

**Temperature Rating:**

450.0 degrees fahrenheit

**Thread Series:**

Unjf

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Head Major Countersink Angle:**

Between 75.75 degrees and 76.25 degrees

**Head Minor Countersink Angle:**

Between 59.75 degrees and 60.25 degrees

**Material:**

Steel comp 304 or steel comp 305

**Material Specification:**

Qq-s-763, cond a federal specification all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response except threads

**Specification Data:**

80205-nas1734 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0