

NSN 5310-01-057-3766 Blind Rivet Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-01-057-3766 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Eliptical countersunk **Head Height:** 0.044 inches **Locking Feature:** Prevailing torque all metal design **Head Major Diameter:** Between 0.518 inches and 0.522 inches **Head Minor Diameter:** Between 0.444 inches and 0.448 inches Lubrication: Dry film lubricant **Nut Style:** Blind rivet w/smooth round shank

**Nut Diameter:** 

Between 0.394 inches and 0.396 inches

**Nut Length:** 

0.768 inches

**Nut Grip Range:** 

+0.220/+0.280 inches

**Shank End Type:** 

Open

**Tempurature Rating:** 

450.0 degrees fahrenheit

**Thread Series:** 

Unif

Thready Qty Per Inch (tpi):

**Thread Size:** 

0.312 inches

**Head Major Countersink Angle:** 

Between 75.75 degrees and 76.25 degrees

**Head Minor Countersink Angle:** 

Between 59.75 degrees and 60.25 degrees

Material:

Steel comp 304 or steel comp 305

**Material Specification:** 

Qq-s-763 cond a federal specification all material responses

## NSN 5310-01-057-3766

A021a0

Blind Rivet Self-locking Nut - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-416 type 2 class 2 federal specification single treatment response except threads
Specification Data:
80205-nas1734 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: