

NSN 5310-01-057-4283 Blind Rivet Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-01-057-4283 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Eliptical countersunk **Head Height:** 0.034 inches **Locking Feature:** Prevailing torque all metal design **Head Major Diameter:** Between 0.329 inches and 0.333 inches **Head Minor Diameter:** Between 0.278 inches and 0.282 inches Lubrication: Dry film lubricant **Nut Style:** Blind rivet w/smooth round shank **Nut Diameter:** Between 0.239 inches and 0.241 inches **Nut Length:** 0.575 inches **Nut Grip Range:** +0.160/+0.220 inches **Shank End Type:** Open **Tempurature Rating:** 450.0 degrees fahrenheit

Thread Series:

Unif

Thready Qty Per Inch (tpi):

Thread Size:

0.190 inches

Head Major Countersink Angle:

Between 75.75 degrees and 76.25 degrees

Head Minor Countersink Angle:

Between 59.75 degrees and 60.25 degrees

Material:

Steel comp 304 or steel comp 305

Material Specification:

Qq-s-763 cond a federal specification all material responses

NSN 5310-01-057-4283

A021a0

Blind Rivet Self-locking Nut - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-416 type 2 class 2 federal specification single treatment response except threads
Specification Data:
80205-nas1734 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: