
Blind Rivet Self-locking Nut - Page 1 of 2





Thread Class: 3b **Thread Direction: Right-hand** Head Style: Eliptical countersunk **Head Height:** 0.040 inches Locking Feature: Prevailing torque all metal design Head Major Diameter: Between 0.436 inches and 0.440 inches **Head Minor Diameter:** Between 0.370 inches and 0.374 inches Lubrication: Dry film lubricant Nut Style: Blind rivet w/smooth round shank Nut Diameter: Between 0.325 inches and 0.327 inches Nut Length: 0.567 inches Nut Grip Range: +0.100/+0.160 inches Shank End Type: Open **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unif Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches Head Major Countersink Angle: Between 75.75 degrees and 76.25 degrees Head Minor Countersink Angle: Between 59.75 degrees and 60.25 degrees Material: Steel comp 304 or steel comp 305 **Material Specification:**

Qq-s-763, cond a federal specification all material responses

NSN 5310-01-057-9358

Blind Rivet Self-locking Nut - Page 2 of 2



Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Specification Data:

80205-nas1734 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A021a0