## NSN 5310-01-058-3723

Spline Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-058-3723

| Thread Class:  |
|--|
| 3b   |
| Thread Direction:  |
| Right-hand   |
| Locking Feature:   |
| Prevailing torque all metal design                                     |
| Pilot Diameter:  |
| Between 0.294 inches and 0.302 inches                                  |
| Pilot Length:  |
| 0.099 inches   |
| Lubrication:   |
| Dry film lubricant   |
| Nut Style:   |
| Spline (floating)  |
| Nut Length:  |
| 0.572 inches   |
| Nut Height:  |
| 0.344 inches   |
| Thread Series:   |
| Unjc   |
| Features Provided:   |
| Floating nut   |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Thread Size:   |
| 0.164 inches   |
| Material:  |
| Steel nut  |
| Material Specification:  |
| Mil-s-7947 military specification single material response bracket     |
| Surface Treatment:   |
| Cadmium nut and chromate nut   |
| Surface Treatment Specification:                                       |
| Qq-p-416, ty2, cl3 federal specification single treatment response nut |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A021a0   |

## NSN 5310-01-058-3723

Spline Self-locking Nut - Page 2 of 2



Mil-std (military Standard):

Mil-s-23195 spec.