

NSN 5310-01-058-3978 Blind Rivet Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-01-058-3978 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Eliptical countersunk **Head Height:** 0.044 inches **Locking Feature:** Prevailing torque all metal design **Head Major Diameter:** Between 0.518 inches and 0.522 inches **Head Minor Diameter:** Between 0.444 inches and 0.448 inches Lubrication: Dry film lubricant **Nut Style:** Blind rivet w/smooth round shank **Nut Diameter:** Between 0.394 inches and 0.396 inches **Nut Length:** 1.138 inches **Nut Grip Range:** +0.100/+0.160 inches **Shank End Type:** Closed **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** 

Unif

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

**Head Major Countersink Angle:** 

Between 75.75 degrees and 76.25 degrees

**Head Minor Countersink Angle:** 

Between 59.75 degrees and 60.25 degrees

Material:

Steel comp 304 or steel comp 305

**Material Specification:** 

Qq-s-763 cond a federal specification all material responses

## NSN 5310-01-058-3978

Blind Rivet Self-locking Nut - Page 2 of 2



Surface	Treatm	ent:
---------	--------	------

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2, class 2 federal specification single treatment response

**Specification Data:** 

80205-nas1735 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_\_

Demilitarization:

No

Fiig:

A021a0