

View Online at <https://aerobasegroup.com/nsn/5310-01-067-8545>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Counterbore Diameter:**

0.220 inches nut

**Overall Height:**

0.515 inches

**Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Nut Style:**

Plate

**Nut Length:**

0.805 inches

**Nut Height:**

0.255 inches

**Plate Thickness:**

Between 0.015 inches and 0.030 inches

**Plate Width:**

0.443 inches

**Nut Counterbore Depth:**

0.070 inches nut

**Nut Mounting Provision:**

Straight holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.290 inches and 0.300 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.588 inches and 0.592 inches

**Temperature Rating:**

Between -88.0 degrees fahrenheit and 450.0 degrees fahrenheit

**Thread Series:**

Unjf

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Material:**

Iron alloy 660 shell

**Material Specification:**

Mil-r-25988 military specification single material response seal

**Precious Material And Location:**

Nut silver

**Precious Material:**

Silver

**Surface Treatment:**

Passivate shell

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response nut

**Specification Data:**

26512-gn502af manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0

**Mil-std (military Standard):**

Mil-r-25988 spec.