

View Online at <https://aerobasegroup.com/nsn/5310-01-070-2114>

**Hole Diameter:**

Between 0.624 inches and 0.633 inches

**Outside Diameter:**

Between 0.990 inches and 1.010 inches

**Material Thickness:**

Between 0.156 inches and 0.166 inches

**Min. Tensile Strength (psi):**

240000 pounds per square inch

**Top Recess Diameter:**

Between 0.714 inches and 0.733 inches

**Bottom Recess Angle:**

Between 89.5 degrees and 90.5 degrees

**Top Recess Angle:**

Between 89.5 degrees and 90.5 degrees

**Bottom Recess Diameter:**

Between 0.714 inches and 0.733 inches

**Surface Finish:**

63.0 microinches top

**Material:**

Steel comp h11

**Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Mil-c-8837, type 2, cl 2 military specification single treatment response

**Style Designator:**

Recessed both sides

**Specification Data:**

97499-140-007 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A022b0

**Mil-std (military Standard):**

Mil-c-8837 spec.