

View Online at <https://aerobasegroup.com/nsn/5310-01-075-2531>

Thread Class:

2b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design or prevailing torque with nonmetallic insert

Lubrication:

Dry film lubricant

Nut Style:

Cap

Nut Height:

0.530 inches

Width Across Flats:

Between 0.489 inches and 0.500 inches

Tempurature Rating:

250.0 degrees fahrenheit

Thread Series:

Unf

Thready Qty Per Inch (tpi):

24

Hardness Rating:

28.0 rockwell c

Thread Size:

0.312 inches

Bearing Surface Type:

Chamfered

Bearing Surface Finish:

110.0 microinches

Material:

Steel comp 1005 nut or steel comp 1006 nut or steel comp 1008 nut or steel comp 1009 nut or steel comp 1010 nut or steel comp 1011 nut or steel comp 1012 nut or steel comp 1013 nut or steel comp 1015 nut or steel comp 1016 nut or steel comp 1017 nut or steel comp 1018 nut or steel comp 1019 nut or steel comp 1020 nut or steel comp 1021 nut or steel comp 1022 nut or steel comp 1023 nut or steel comp 1524 nut or steel comp 1025 nut or steel comp 1026 nut or steel comp 1527 nut or steel comp 1029 nut or steel comp 1030 nut or steel comp 1033 nut or steel comp 1034 nut or steel comp 1035 nut or steel comp 1536 nut or steel comp 1037 nut or steel comp 1038 nut or steel comp 1039 nut or steel comp 1040 nut or steel comp 1541 nut

Surface Treatment:

Passivate except insert

Surface Treatment Specification:

Qq-p-35, type 2 federal specification single treatment response except insert

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No