

View Online at <https://aerobasegroup.com/nsn/5310-01-075-2532>

Thread Class:

2b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design or prevailing torque with nonmetallic insert

Lubrication:

Dry film lubricant

Nut Style:

Cap

Nut Height:

0.340 inches

Width Across Flats:

Between 0.302 inches and 0.312 inches

Tempurature Rating:

250.0 degrees fahrenheit

Thread Series:

Unc

Thready Qty Per Inch (tpi):

32

Hardness Rating:

28.0 rockwell c

Thread Size:

0.164 inches

Bearing Surface Type:

Chamfered

Bearing Surface Finish:

110.0 microinches

Material:

Steel comp 1005 nut or steel comp 1006 nut or steel comp 1008 nut or steel comp 1009 nut or steel comp 1010 nut or steel comp 1011 nut or steel comp 1012 nut or steel comp 1013 nut or steel comp 1015 nut or steel comp 1016 nut or steel comp 1017 nut or steel comp 1018 nut or steel comp 1019 nut or steel comp 1020 nut or steel comp 1021 nut or steel comp 1022 nut or steel comp 1023 nut or steel comp 1524 nut or steel comp 1025 nut or steel comp 1026 nut or steel comp 1527 nut or steel comp 1029 nut or steel comp 1030 nut or steel comp 1033 nut or steel comp 1034 nut or steel comp 1035 nut or steel comp 1536 nut or steel comp 1037 nut or steel comp 1038 nut or steel comp 1039 nut or steel comp 1040 nut or steel comp 1541 nut

Material Specification:

Sae assn standard single material response nut

Surface Treatment:

Cadmium except insert and chromate except insert

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses except insert

Shelf Life:

N/a

Unit Of Measure:

Fig:

A021a0