## NSN 5310-01-075-7123

Plate Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-075-7123 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 0.240 inches nut Lubrication: Dry film lubricant **Overall Height:** 0.380 inches **Mounting Hole Diameter:** Between 0.098 inches and 0.103 inches **Nut Style:** Plate **Nut Length:** 0.995 inches **Nut Height:** 0.237 inches **Plate Thickness:** 0.035 inches Plate Width: 0.522 inches **Nut Counterbore Depth:** 0.070 inches nut **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** Between 0.339 inches and 0.349 inches **Center To Center Distance Between Mounting Holes Along Length:** Between 0.686 inches and 0.690 inches **Thread Series:** Unif **Features Provided:** Thready Qty Per Inch (tpi):

Floating nut 32 **Thread Size:** 0.190 inches

# NSN 5310-01-075-7123

Plate Self-locking Nut - Page 2 of 2



NЛ	ate	ria	ı.
IVI	ale	па	I -

Steel comp 1045 shell or steel comp 4130 shell

### **Material Specification:**

Aisi assn standard 1st material response washer or mil-s-18729 military specification 2nd material response washer

#### **Surface Treatment:**

Cadmium and chromate

### **Surface Treatment Specification:**

Qq-p-416, type 2 class 2 federal specification all treatment responses

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-s-18729 spec.