## NSN 5310-01-080-3440

Round Self-locking Nut - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-01-080-3440

| Thread Pitch Diameters:                   |
|---|
| +0.3707/+0.3733 inches                    |
| Thread Direction:                         |
| Right-hand                                |
| Locking Feature:                          |
| Prevailing torque with nonmetallic insert |
| Small End Diameter:                       |
| 0.625 inches                              |
| Drive Point Depth:                        |
| Between 0.088 inches and 0.096 inches     |
| Nut Style:                                |
| Round                                     |
| Nut Diameter:                             |
| Between 0.735 inches and 0.750 inches     |
| Nut Thickness:                            |
|   |
| Between 0.250 inches and 0.282 inches     |
| Drive Point Width:                        |
| Between 0.105 inches and 0.135 inches     |
| Undercut Thickness:                       |
| 0.094 inches                              |
| Drive Point Quantity:                     |
| 4   |
| Tempurature Rating:                       |
| 350.0 degrees fahrenheit                  |
| Thread Series:                            |
| Uns                                       |
| Thready Qty Per Inch (tpi):               |
| 32  |
| Thread Size:                              |
| 0.391 inches                              |
| Material:                                 |
| Steel comp 303 nut                        |
| Surface Treatment:                        |
| Passivate except insert                   |
| Shelf Life:                               |
| N/a                                       |
| Unit Of Measure:                          |
|   |
| Demilitarization:                         |
| No  |
| Fiig:                                     |

A021a0