

View Online at <https://aerobasegroup.com/nsn/5310-01-083-4119>

Mounting Hole Diameter:

Between 0.104 inches and 0.114 inches

Nut Style:

Plate nut spacer

Nut Length:

Between 0.905 inches and 0.949 inches

Thru-hole Diameter:

Between 0.463 inches and 0.473 inches

Plate Thickness:

Between 0.032 inches and 0.038 inches

Plate Width:

Between 0.540 inches and 0.560 inches

Nut Mounting Provision:

Countersunk holes

Mounting Provision Location:

Nut projection side

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.342 inches and 0.344 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.685 inches and 0.689 inches

Mounting Hole Countersink Angle:

Between 0.098 degrees and 102.0 degrees

Special Features:

Removable shim bonded to spacer on countersink side

Material:

Steel comp 302 or steel comp 304

Material Specification:

Qq-s-766, cond a federal specification all material responses

Surface Treatment:

Plastic

Surface Treatment Specification:

Mil-p-23377 military specification single treatment response

Specification Data:

26512-gs540h manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0

Mil-std (military Standard):

Mil-p-23377 spec.