Hexagon Self-locking Nut - Page 1 of 2



2nd material response

View Online at https://aerobasegroup.com/nsn/5310-01-084-5416

-	Thread Class:
3	b
т	hread Direction:
F	Right-hand
L	ocking Feature:
F	Prevailing torque all metal design
C	Counterbore Diameter:
0	0.210 inches nut and 0.215 inches nut
L	ubrication:
C	Dry film lubricant
N	lut Height:
0	0.245 inches
Ν	lut Counterbore Depth:
0	0.107 inches nut and 0.117 inches nut
۷	Vidth Across Flats:
E	Between 0.243 inches and 0.251 inches
Т	empurature Rating:
4	50.0 degrees fahrenheit
Т	Thread Series:
ι	Jnjf
Т	hready Qty Per Inch (tpi):
3	2
T	hread Size:
0	0.190 inches
E	Bearing Surface Type:
F	lat
N	Naterial:
ຣ	Steel comp 4340 or steel comp 8740
N	Naterial Specification:
Ν	Ail-s-6049 military specification 1st material response or mil-s-5000 military specification
S	Surface Treatment:
C	Cadmium
S	Surface Treatment Specification:
Α	Ams 2401 assn standard single treatment response
S	Shelf Life:
Ν	l/a
ι	Jnit Of Measure:
	-
C	Demilitarization:
Ν	10
F	iig:
Δ	\021a0

NSN 5310-01-084-5416

Hexagon Self-locking Nut - Page 2 of 2



Mil-std (military Standard):

Mil-s-6049 spec.