

View Online at <https://aerobasegroup.com/nsn/5310-01-087-0764>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.194 inches nut

Lubrication:

Dry film lubricant

Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Nut Style:

Plate

Nut Length:

0.745 inches

Nut Height:

0.375 inches

Plate Thickness:

Between 0.020 inches and 0.030 inches

Plate Width:

0.416 inches

Nut Counterbore Depth:

0.188 inches nut

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.245 inches and 0.255 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.498 inches and 0.502 inches

Temperature Rating:

450.0 degrees fahrenheit

Thread Series:

Unjf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Material:

Steel comp 1030 shell or steel comp 1035 shell or steel comp 1536 shell or steel comp 1039 shell or steel comp 1040 shell or steel comp 1541 shell or steel comp 1042 shell or steel comp 1043 shell or steel comp 1045 shell or steel comp 1046 shell or steel comp 1548 shell or steel comp 1049 shell or steel comp 1050 shell or steel comp 1551 shell or steel comp 1552 shell or steel comp 1053 shell or steel comp 1055 shell or steel comp 1059 shell or steel comp 1060 shell or steel comp 1561 shell or steel comp 1065 shell or steel comp 1566 shell or steel comp 1069 shell or steel comp 1070 shell

Material Specification:

Sae assn standard all material responses shell

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, class 2 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0