## NSN 5310-01-088-1999

Lock Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-01-088-1999 **Hole Diameter:** Between 0.168 inches and 0.178 inches **Outside Diameter:** 0.280 inches **Material Thickness:** Between 0.031 inches and 0.037 inches Hardness Rating: Between 45.0 rockwell c and 53.0 rockwell c **Criticality Code Justification:** Zzzw **Special Features:** Free of mercury contamination Material: Steel comp 1060 or steel comp 1561 or steel comp 1065 or steel comp 1566 or steel comp 1069 or steel comp 1070 or steel comp 1572 or steel comp 1074 or steel comp 1075 or steel comp 1080 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Cadmium **Special Test Features:** Special quality control testing **Surface Treatment Specification:** Qq-p-416 cl 3 type 1 federal specification single treatment response **Style Designator:** Split helical-right hand **Test Data Document:** 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Or Standard:** A class and 1 style **Departure From Cited Document:** As differentiated by material which must conform to ships parts control center special quality control provisions Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A022b0