

View Online at <https://aerobasegroup.com/nsn/5310-01-090-5556>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Counterbore Diameter:**

0.254 inches nut

**Lubrication:**

Dry film lubricant

**Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Nut Style:**

Plate

**Nut Length:**

1.292 inches

**Nut Height:**

0.543 inches

**Plate Thickness:**

Between 0.027 inches and 0.037 inches

**Plate Width:**

0.547 inches

**Removable Nut Manufacturer Code:**

80205

**Nut Counterbore Depth:**

0.313 inches nut

**Nut Mounting Provision:**

Straight holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.495 inches and 0.505 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.998 inches and 1.002 inches

**Removable Nut Manufacturer Part Number:**

Nas1794c4-5

**Temperature Rating:**

450.0 degrees fahrenheit

**Thread Series:**

Unjf

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Material:**

Iron alloy 660 shell

**Material Specification:**

Ams 5525 assn standard single material response shell

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Specification Data:**

80205-nas1791 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0