

View Online at <https://aerobasegroup.com/nsn/5310-01-090-6367>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.254 inches nut

Lubrication:

Dry film lubricant

Mounting Hole Diameter:

Between 0.098 inches and 0.103 inches

Nut Style:

Plate

Nut Length:

1.292 inches

Nut Height:

0.481 inches

Plate Thickness:

Between 0.027 inches and 0.037 inches

Plate Width:

0.547 inches

Removable Nut Manufacturer Code:

80205

Nut Counterbore Depth:

0.250 inches nut

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.495 inches and 0.505 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.998 inches and 1.002 inches

Removable Nut Manufacturer Part Number:

Nas1794c4-4

Tempurature Rating:

450.0 degrees fahrenheit

Thread Series:

Unjf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Material:

Iron alloy 660 shell

Material Specification:

Ams 5525 assn standard single material response shell

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Specification Data:

80205-nas1791 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0