## NSN 5310-01-092-8740

Recessed Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-01-092-8740

Hole Diameter	r:
Between 0.624	ļ

Between 0.624 inches and 0.633 inches

**Outside Diameter:** 

Between 1.052 inches and 1.072 inches

**Material Thickness:** 

Between 0.183 inches and 0.193 inches

Min. Tensile Strength (psi):

240000 pounds per square inch

**Top Recess Diameter:** 

Between 0.744 inches and 0.763 inches

**Bottom Recess Angle:** 

Between 89.5 degrees and 90.5 degrees

**Top Recess Angle:** 

Between 89.5 degrees and 90.5 degrees

**Bottom Recess Diameter:** 

Between 0.744 inches and 0.763 inches

**Surface Finish:** 

63.0 microinches top

Material:

Steel comp h11

## **Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

**Surface Treatment:** 

Cadmium and chromate

## **Surface Treatment Specification:**

Mil-c-8837, type 2, cl 2 military specification single treatment response

**Style Designator:** 

Recessed both sides

**Specification Data:** 

97499-140-007 manufacturers standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A022b0

## Mil-std (military Standard):

Mil-c-8837 spec.