

View Online at <https://aerobasegroup.com/nsn/5310-01-094-2887>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.317 inches nut

Lubrication:

Dry film lubricant

Mounting Hole Diameter:

Between 0.130 inches and 0.135 inches

Nut Style:

Plate

Nut Length:

1.292 inches

Nut Height:

0.344 inches

Plate Thickness:

Between 0.035 inches and 0.045 inches

Plate Width:

0.643 inches

Removable Nut Manufacturer Code:

80205

Nut Counterbore Depth:

0.070 inches nut

Nut Mounting Provision:

Straight holes

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.495 inches and 0.505 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.998 inches and 1.002 inches

Removable Nut Manufacturer Part Number:

Nas1794a5-1

Thread Series:

Unjf

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Material:

Steel shell

Surface Treatment:

Cadmium shell and chromate shell

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses shell

Specification Data:

80205-nas1791 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0