

View Online at <https://aerobasegroup.com/nsn/5310-01-107-4376>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Lubrication:

Dry film lubricant

Nut Style:

Single ball seat, double hexagon

Ball Seat Radius:

Between 0.240 inches and 0.245 inches

Nut Height:

Between 0.274 inches and 0.284 inches

Width Across Flats:

Between 0.243 inches and 0.251 inches

Tempurature Rating:

450.0 degrees fahrenheit

Thread Series:

Unjf

Thready Qty Per Inch (tpi):

32

Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

Thread Size:

0.190 inches

Special Features:

L0.252 in. Min and 0.258 in. Maximum washer id, 0.375 in. Min and 0.385 in. Maximum washer od, 0.038 in. Nom washer thickness, 0.042 in. Min and 0.052 in. Maximum shoulder height, 0.240 in. Min and 0.245 in. Maximum sphgrical radius

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-s-5000 spec.