

View Online at <https://aerobasegroup.com/nsn/5310-01-108-2539>

Thread Class:

3b

Thread Direction:

Right-hand

Washer Outside Diameter:

Between 1.465 inches and 1.495 inches

Counterbore Diameter:

1.055 inches nut and 1.065 inches nut

Overall Height:

Between 1.018 inches and 1.058 inches

Nut Style:

Flat with turned back edge

Nut Counterbore Depth:

0.475 inches nut and 0.495 inches nut

Width Across Flats:

Between 1.239 inches and 1.252 inches

Tempurature Rating:

450.0 degrees fahrenheit

Thread Series:

Unjf

Thready Qty Per Inch (tpi):

14

Hardness Rating:

Between 80.0 rockwell b and 32.0 rockwell c

Thread Size:

0.875 inches

Bearing Surface Finish:

125.0 microinches

Material:

Steel comp 1005 nut or steel comp 1006 nut or steel comp 1008 nut or steel comp 1009 nut or steel comp 1010 nut or steel comp 1011 nut or steel comp 1012 nut or steel comp 1013 nut or steel comp 1015 nut or steel comp 1016 nut or steel comp 1017 nut or steel comp 1018 nut or steel comp 1019 nut or steel comp 1020 nut or steel comp 1021 nut or steel comp 1022 nut or steel comp 1023 nut or steel comp 1524 nut or steel comp 1025 nut or steel comp 1026 nut or steel comp 1527 nut or steel comp 1029 nut or steel comp 1030 nut or steel comp 1033 nut or steel comp 1034 nut or steel comp 1035 nut or steel comp 1536 nut or steel comp 1037 nut or steel comp 1038 nut or steel comp 1039 nut or steel comp 1040 nut or steel comp 1541 nut

Material Specification:

Sae assn standard all material responses nut

Surface Treatment:

Passivate washer

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses nut

Shelf Life:

N/a

Unit Of Measure:

Fig:

A021a0