

View Online at <https://aerobasegroup.com/nsn/5310-01-111-9445>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Counterbore Diameter:**

0.254 inches nut

**Lubrication:**

Dry film lubricant

**Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Nut Style:**

Plate

**Nut Length:**

1.306 inches

**Nut Height:**

0.419 inches

**Plate Thickness:**

Between 0.027 inches and 0.037 inches

**Plate Width:**

0.547 inches

**Removable Nut Manufacturer Code:**

80205

**Nut Counterbore Depth:**

0.188 inches nut

**Nut Mounting Provision:**

Straight holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

Between 0.495 inches and 0.505 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.310 inches and 0.314 inches

**Removable Nut Manufacturer Part Number:**

Nas1794

**Thread Series:**

Unjf

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Material:**

Steel shell

**Surface Treatment:**

Cadmium shell and chromate shell

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification all treatment responses nut

**Specification Data:**

80205-nas1792 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0