

View Online at <https://aerobasegroup.com/nsn/5310-01-112-1762>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Counterbore Diameter:

0.372 inches nut and 0.382 inches nut

Lubrication:

Soluble lubricant

Mounting Hole Diameter:

Between 0.130 inches and 0.135 inches

Nut Style:

Plate

Nut Length:

1.292 inches

Nut Height:

0.328 inches

Plate Thickness:

0.045 inches

Plate Width:

Between 0.412 inches and 0.609 inches

Nut Counterbore Depth:

0.062 inches nut

Nut Mounting Provision:

Countersunk holes or dimpled holes

Mounting Provision Location:

Opposite nut projection side

Mounting Hole Arrangement Style:

2 holes

Distance From Aperture Center To Mounting Hole Center:

Between 0.495 inches and 0.505 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.998 inches and 1.002 inches

Tempurature Rating:

450.0 degrees fahrenheit

Thread Series:

Un

Features Provided:

Floating nut

Thready Qty Per Inch (tpi):

28

Thread Size:

0.312 inches

Mounting Hole Countersink Angle:

Between 98.0 degrees and 102.0 degrees

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0