

NSN 5310-01-112-4381 Blind Rivet Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-01-112-4381 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Eliptical countersunk **Head Height:** 0.034 inches **Locking Feature:** Prevailing torque all metal design **Head Major Diameter:** Between 0.329 inches and 0.333 inches **Head Minor Diameter:** Between 0.278 inches and 0.282 inches Lubrication: Dry film lubricant **Nut Style:** Blind rivet w/smooth round shank **Nut Diameter:** Between 0.239 inches and 0.241 inches **Nut Length:** 0.635 inches **Nut Grip Range:** +0.220/+0.280 inches **Shank End Type:** Open

**Tempurature Rating:** 

450.0 degrees fahrenheit

**Thread Series:** 

Unif

Thready Qty Per Inch (tpi):

22

Thread Size:

0.190 inches

**Head Major Countersink Angle:** 

Between 75.75 degrees and 76.25 degrees

**Head Minor Countersink Angle:** 

Between 59.75 degrees and 60.25 degrees

Material:

Steel comp 304 or steel comp 305

**Material Specification:** 

Qq-s-763, cond a federal specification all material responses

## NSN 5310-01-112-4381

Blind Rivet Self-locking Nut - Page 2 of 2



Surface Treatment	Sι
-------------------	----

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl 2 federal specification all treatment responses

**Specification Data:** 

80205-nas1734 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A021a0