

View Online at <https://aerobasegroup.com/nsn/5310-01-113-9819>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design or prevailing torque with nonmetallic insert

Pilot Diameter:

Between 0.321 inches and 0.325 inches

Pilot Length:

Between 0.298 inches and 0.328 inches

Lubrication:

Dry film lubricant

Nut Style:

Spline

Nut Diameter:

Between 0.423 inches and 0.458 inches

Nut Height:

Between 0.455 inches and 0.515 inches

Tempurature Rating:

250.0 degrees fahrenheit

Thread Series:

Unf

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Material:

Steel comp 1013 nut or steel comp 1015 nut or steel comp 1016 nut or steel comp 1017 nut or steel comp 1018 nut or steel comp 1019 nut or steel comp 1020 nut or steel comp 1021 nut or steel comp 1022 nut or steel comp 1023 nut or steel comp 1524 nut or steel comp 1025 nut or steel comp 1026 nut or steel comp 1527 nut or steel comp 1029 nut or steel comp 1030 nut or steel comp 1033 nut or steel comp 1035 nut or steel comp 1536 nut or steel comp 1037 nut or steel comp 1038 nut or steel comp 1039 nut or steel comp 1040 nut or steel comp 1541 nut

Surface Treatment:

Cadmium except insert and chromate except insert

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses except insert

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0