NSN 5310-01-114-5174

Assembled Washer Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-114-5174 **Thread Class:** 3b **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Washer Outside Diameter:** 0.660 inches **Counterbore Diameter:** 0.412 inches nut and 0.417 inches nut **Overall Height:** 0.355 inches **Nut Style:** Flat with turned up edge **Nut Counterbore Depth:** 0.087 inches nut and 0.097 inches nut Width Across Flats: Between 0.430 inches and 0.439 inches **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unjf Thready Qty Per Inch (tpi): Hardness Rating: Between 39.0 rockwell c and 48.0 rockwell c **Thread Size:** 0.375 inches **Special Features:** Rockwell c scale 40 min and rockwell c scale 45 maximum washer Material: Steel washer **Material Specification:** Mil-s-5626 military specification 1st material response nut or mil-s-5000 military specification 2nd material response nut or mil-s-6049 military specification 3rd material response nut **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification all treatment responses Shelf Life:

--

N/a

Unit Of Measure:

NSN 5310-01-114-5174

Assembled Washer Self-locking Nut - Page 2 of 2



Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-s-5626 spec.