## NSN 5310-01-115-4477



Plate Self-locking Nut - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5310-01-115-4477 **Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Counterbore Diameter:** 6.5 millimeters nut Lubrication: Dry film lubricant **Mounting Hole Diameter:** Between 2.5 millimeters and 2.7 millimeters **Nut Style:** Plate **Nut Length:** 30.0 millimeters **Nut Height:** Between 7.3 millimeters and 8.1 millimeters **Plate Thickness:** 0.7 millimeters Plate Width: 13.1 millimeters **Nut Counterbore Depth:** 2.7 millimeters nut **Nut Mounting Provision:** Straight holes **Mounting Hole Arrangement Style:** 2 holes **Distance From Aperture Center To Mounting Hole Center:** 11.0 millimeters **Center To Center Distance Between Mounting Holes Along Length:** 8.0 millimeters **Tempurature Rating:** 235.0 degrees celsius **Thread Series:** Μį **Features Provided:** Floating nut **Thread Size:** 6.0 millimeters **Thread Pitch In Millimeters:** 

1.00 **Thread Tolerance Class:** 

4h5h internal

## NSN 5310-01-115-4477

Plate Self-locking Nut - Page 2 of 2

A021a0



Material:
Steel
Surface Treatment:
Cadmium and chromate or cadmium and phosphate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification 1st treatment response or qq-p-416, type 3, cl 2 federal specification 2nd treatment response
Specification Data:
80205-na0073 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig: