

View Online at <https://aerobasegroup.com/nsn/5310-01-116-3579>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Washer Outside Diameter:**

0.660 inches

**Counterbore Diameter:**

0.407 inches nut and 0.417 inches nut

**Lubrication:**

Dry film lubricant

**Overall Height:**

Between 0.341 inches and 0.361 inches

**Nut Style:**

Flat with turned up edge

**Nut Counterbore Depth:**

0.072 inches nut and 0.087 inches nut

**Width Across Flats:**

Between 0.430 inches and 0.439 inches

**Temperature Rating:**

450.0 degrees fahrenheit

**Thread Series:**

Unjf

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

Between 36.0 rockwell c and 40.0 rockwell c

**Thread Size:**

0.375 inches

**Special Features:**

Washer rockwell c scale 40 min and rockwell c scale 45 max

**Material:**

Steel comp 4340 nut or steel comp 8740 nut

**Material Specification:**

Mil-s-5000 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification all treatment responses

**Specification Data:**

80205-nas1726 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0

**Mil-std (military Standard):**

Mil-s-5000 spec.