NSN 5310-01-119-6793

Assembled Washer Self-locking Nut - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5310-01-119-6793 **Thread Class: Thread Direction:** Right-hand **Locking Feature:** Prevailing torque all metal design **Washer Outside Diameter:** 0.340 inches **Counterbore Diameter:** 0.197 inches nut and 0.202 inches nut **Overall Height:** 0.240 inches **Nut Style:** Flat with turned up edge **Nut Counterbore Depth:** 0.087 inches nut and 0.097 inches nut Width Across Flats: Between 0.212 inches and 0.220 inches **Tempurature Rating:** 450.0 degrees fahrenheit **Thread Series:** Unjc Thready Qty Per Inch (tpi): Hardness Rating: Between 39.0 rockwell c and 43.0 rockwell c **Thread Size:** 0.164 inches **Special Features:** Washer rockwell c scale 40.0 min and rockwell c scale 45.0 max Steel comp 8740 or steel comp 4340 or steel comp 4140 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5626 military specification 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2 cl2 military specification single treatment response Shelf Life:

--

N/a

Unit Of Measure:

NSN 5310-01-119-6793

Assembled Washer Self-locking Nut - Page 2 of 2



_		••	• •				
n	em	ш	112	riz	2 †1	n	٠.

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-s-6049 spec.