

View Online at <https://aerobasegroup.com/nsn/5310-01-120-5126>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Lubrication:**

Dry film lubricant

**Mounting Hole Diameter:**

Between 0.098 inches and 0.103 inches

**Nut Style:**

Plate

**Nut Length:**

0.927 inches

**Nut Height:**

Between 0.432 inches and 0.472 inches

**Plate Thickness:**

Between 0.020 inches and 0.030 inches

**Plate Width:**

Between 0.420 inches and 0.460 inches

**Removable Nut Manufacturer Code:**

29372

**Nut Mounting Provision:**

Straight holes

**Mounting Hole Arrangement Style:**

2 holes

**Distance From Aperture Center To Mounting Hole Center:**

0.344 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.685 inches and 0.689 inches

**Removable Nut Manufacturer Part Number:**

Ca35425-4-1

**Thread Series:**

Unf

**Features Provided:**

Floating nut

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Material:**

Steel comp 630 nut

**Material Specification:**

Ams5643 assn standard single material response nut

**Surface Treatment:**

Passivate shell

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shell

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0