NSN 5310-01-121-5526

Plate Self-locking Nut - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5310-01-121-5526

| 2b |
|---|
| Thread Direction: |
| Right-hand |
| Locking Feature: |
| Prevailing torque with metallic insert |
| Mounting Hole Diameter: |
| Between 0.128 inches and 0.135 inches |
| Nut Style: |
| Plate |
| Nut Length: |
| Between 0.975 inches and 0.995 inches |
| Nut Height: |
| Between 1.980 inches and 2.020 inches |
| Plate Thickness: |
| Between 0.050 inches and 0.070 inches |
| Plate Width: |
| Between 0.386 inches and 0.406 inches |
| Nut Mounting Provision: |
| Straight holes |
| Mounting Hole Arrangement Style: |
| 2 holes |
| Distance From Aperture Center To Mounting Hole Center: |
| 0.344 inches |
| Center To Center Distance Between Mounting Holes Along Length: |
| Between 0.686 inches and 0.690 inches |
| Thread Series: |
| Unf |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.190 inches |
| Material: |
| Steel comp 304 locking insert |
| Material Specification: |
| Mil-a-12545, t6 military specification single material response except insert |
| Surface Treatment: |
| Cadmium locking insert and chromate locking insert |
| Surface Treatment Specification: |
| Qq-p-416, type 2 federal specification single treatment response locking insert |
| Shelf Life: |
| N/a |

NSN 5310-01-121-5526

Plate Self-locking Nut - Page 2 of 2



| | | • - | | | | | | |
|---|-----|-----|----|-----|----|----|----|----|
| | In | | Of | RЛ | മാ | CI | ır | Δ. |
| L | ,,, | | | IVI | ca | | | |

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-12545 spec.