

View Online at <https://aerobasegroup.com/nsn/5310-01-123-1776>

Thread Class:

2b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque all metal design

Nut Style:

Hexagon

Nut Height:

Between 0.833 inches and 0.885 inches

Width Across Flats:

Between 1.394 inches and 1.438 inches

Thread Series:

Unc

Thready Qty Per Inch (tpi):

9

Thread Size:

0.875 inches

Bearing Surface Type:

Chamfered

Special Features:

Tab on bearing surface peened on threads

Material:

Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541

Material Specification:

Astm a194 grade 1 or 2 or 2h or 2hm assn standard all material responses

Surface Treatment:

Zinc

Surface Treatment Specification:

Astm a153 assn standard single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A021a0