# NSN 5310-01-125-1230

Recessed Washer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5310-01-125-1230

## Hole Diameter:

Between 0.517 inches and 0.522 inches

## **Outside Diameter:**

0.812 inches

## Material Thickness:

Between 0.070 inches and 0.080 inches

## Min. Tensile Strength (psi):

125000 pounds per square inch

#### Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

## **Top Recess Diameter:**

Between 0.625 inches and 0.640 inches

## Bottom Recess Angle:

15.0 degrees

## **Top Recess Angle:**

15.0 degrees

## **Bottom Recess Diameter:**

Between 0.625 inches and 0.640 inches

## **Product Name:**

Navy special project

## Material:

Steel comp 4130

## **Material Specification:**

Mil-s-18729 military specification single material response

## Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

## Style Designator:

Recessed both sides

#### Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# Fiig:

A022b0

## Mil-std (military Standard):

Mil-s-18729 spec.