

View Online at <https://aerobasegroup.com/nsn/5310-01-127-2242>

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque with nonmetallic insert

**Small End Diameter:**

Between 39.20 millimeters and 39.95 millimeters

**Drive Point Depth:**

2.4 millimeters

**Nut Style:**

Round

**Nut Diameter:**

44.575 millimeters

**Nut Thickness:**

Between 11.1 millimeters and 11.9 millimeters

**Drive Point Width:**

4.5 millimeters

**Undercut Thickness:**

2.7 millimeters

**Drive Point Quantity:**

6

**Thread Series:**

M

**Thread Size:**

30.0 millimeters

**Thread Pitch In Millimeters:**

1.50

**Countersink Angle:**

90.0 degrees second end and 120.0 degrees second end

**Thread Tolerance Class:**

5h internal

**Special Features:**

Locking insert, esna color red, shur-lok color natural

**Material:**

Steel comp 1015 nut or steel comp 1020 nut or steel comp 1035 nut or steel comp 1212 nut or steel comp 1213 nut or steel comp 1117 nut or steel comp 1118 nut

**Surface Treatment:**

Phosphate nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A021a0