# NSN 5310-01-128-5142


Plate Self-locking Nut - Page 1 of 2

**Thread Class:** 

2b

Unf

32





### **Thread Direction: Right-hand** Locking Feature: Prevailing torque with metallic insert Mounting Hole Diameter: Between 0.123 inches and 0.133 inches Nut Style: Plate Nut Length: 1.370 inches **Distance From Base To Center Of Aperture:** Between 0.300 inches and 0.320 inches Nut Height: 1.310 inches **Plate Thickness:** Between 0.040 inches and 0.060 inches Plate Width: 1.570 inches **Nut Mounting Provision:** Straight holes Mounting Hole Arrangement Style: 2 holes **Distance From Mounting Hole Center To Base:** 0.250 inches Center To Center Distance Between Mounting Holes Along Width: Between 0.990 inches and 1.010 inches **Tempurature Rating:** 300.0 degrees fahrenheit **Thread Series:** Thready Qty Per Inch (tpi): **Thread Size:** 0.190 inches Material: Stainless steel locking insert **Material Specification:** Qq-a-637, t6 federal specification all material responses except insert Surface Treatment: Chromate except insert

## NSN 5310-01-128-5142

Plate Self-locking Nut - Page 2 of 2



#### Surface Treatment Specification:

Mil-c-5541 military specification single treatment response except insert

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A021a0

#### Mil-std (military Standard):

Mil-c-5541 spec.