

View Online at <https://aerobasegroup.com/nsn/5310-01-130-4274>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque all metal design

**Lubrication:**

Dry film lubricant

**Nut Style:**

Hexagon

**Nut Height:**

Between 0.535 inches and 0.559 inches

**Width Across Flats:**

Between 0.922 inches and 0.940 inches

**Thread Series:**

Unc

**Thready Qty Per Inch (tpi):**

11

**Thread Size:**

0.625 inches

**Bearing Surface Type:**

Chamfered

**Material:**

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541

**Material Specification:**

Gm 301-m, fscm 24617 mfr ref single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Gm 4341-m, fscm 24617 mfr ref single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0