

View Online at <https://aerobasegroup.com/nsn/5310-01-131-2947>

Thread Class:

3b

Thread Direction:

Right-hand

Locking Feature:

Prevailing torque with nonmetallic insert

Counterbore Diameter:

2.075 inches washer and 2.085 inches washer

Small End Diameter:

2.260 inches

Drive Point Depth:

2.280 inches

Nut Style:

Round

Nut Diameter:

Between 2.255 inches and 2.265 inches

Nut Thickness:

Between 0.495 inches and 0.505 inches

Drive Point Width:

0.350 inches

Undercut Thickness:

0.210 inches

Drive Point Quantity:

12

Nut Counterbore Depth:

0.095 inches washer and 0.105 inches washer

Thread Series:

Unj

Thready Qty Per Inch (tpi):

16

Thread Size:

2.000 inches

Bearing Surface Finish:

63.0 microinches

Special Features:

Extended washer on bearing surface 0.090 in. Thick and 2.800 in. Diameter

Material:

Plastic polyethylene terephthalate locking insert

Material Specification:

Qq-a-225/6, t851 federal specification single material response except insert

Surface Treatment:

Anodize except insert

Surface Treatment Specification:

Mil-a-8625, type 2, class 2 military specification single treatment response except insert

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A021a0

Mil-std (military Standard):

Mil-a-8625 spec.