

View Online at <https://aerobasegroup.com/nsn/5310-01-131-2947>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Locking Feature:**

Prevailing torque with nonmetallic insert

**Counterbore Diameter:**

2.075 inches washer and 2.085 inches washer

**Small End Diameter:**

2.260 inches

**Drive Point Depth:**

2.280 inches

**Nut Style:**

Round

**Nut Diameter:**

Between 2.255 inches and 2.265 inches

**Nut Thickness:**

Between 0.495 inches and 0.505 inches

**Drive Point Width:**

0.350 inches

**Undercut Thickness:**

0.210 inches

**Drive Point Quantity:**

12

**Nut Counterbore Depth:**

0.095 inches washer and 0.105 inches washer

**Thread Series:**

Unj

**Thready Qty Per Inch (tpi):**

16

**Thread Size:**

2.000 inches

**Bearing Surface Finish:**

63.0 microinches

**Special Features:**

Extended washer on bearing surface 0.090 in. Thick and 2.800 in. Diameter

**Material:**

Plastic polyethylene terephthalate locking insert

**Material Specification:**

Qq-a-225/6, t851 federal specification single material response except insert

**Surface Treatment:**

Anodize except insert

**Surface Treatment Specification:**

Mil-a-8625, type 2, class 2 military specification single treatment response except insert

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A021a0

**Mil-std (military Standard):**

Mil-a-8625 spec.